

WORK PLATFORM

LTWP1214

TURKUAZ
MACHINERY CA

LTMG

Leading Technology, Mission Global

Product Specifications

Standard Specifications

- ▶ Proportional Control
- ▶ Automatic Pothole Protection
- ▶ Platform Self-Locking Door
- ▶ Full-Stroke Travelling
- ▶ Non-Marking Tyres
- ▶ 4X2 Drive
- ▶ Extended Platform
- ▶ GPS Positioning Buzzer
- ▶ Horn Operating Schedule
- ▶ Safety Access Support Bar
- ▶ Strobe Light
- ▶ Automatic braking system
- ▶ Emergency descent system
- ▶ Emergency stop button
- ▶ Fuel line explosion-proof system
- ▶ Fault diagnosis system
- ▶ Tilt protection system
- ▶ Charging protection system
- ▶ Remote locking system
- ▶ Standard transport forklift holes
- ▶ Folding fence crash bar
- ▶ Continuously variable speed

Product Characteristics

- ▶ The foot-operated extension platform can be spread to the working point quickly.
- ▶ Foldable fence reduces the size of the machine.
- ▶ Convenient to work in narrow space.
- ▶ 25% climbing ability, can climb up the slope smoothly.
- ▶ Swivel chassis for easy maintenance.
- ▶ Automatic fault code display for easy maintenance.



Parameters

Model	LTWP1214
Dimension	
Maximum working height	13.8m
Maximum platform height	11.8m
Size of working platform(L×W×H)	2.23x1.13x1.1m
Overall dimensions(L×W×H, guardrail not folded)	2.47x1.19x2.59m
Overall dimensions (L×W×H, guardrail folded)	2.47x1.19x2.07m
Table extension size	0.9m
Minimum Ground Clearance	0.1/0.002m
Wheelbase	1.89m
Performances	
Safe working load	320kg
Safe working load of the extension platform	113kg
Turning radius (inner/outer wheels)	0/2.2m
Lifting/driving motor	24V/4.5KW
Lifting speed	3-5m/min
Machine travelling speed (stowed state)	3.5km/h
Machine travelling speed (lifting state)	0.8km/h
Maximum climbing capacity	25%
Maximum permissible angle of operation	1.5°/3°
Tires	Ø381x127mm
Power	
Battery	4x6V/200ah
Li-ion battery (optional)	24V/200ah
Charger	24V/30A
Weight	
Weight	2860kg



web

LTMG MACHINERY GROUP CO., LTD.

Tel: 0086-592-5681408

E-mail: info@ltmg.com

Web: www.ltmg.com